

AUTOSLIDE™ OPERATING GUIDE

USER OPERATING MODES

Once the door is operating correctly the desired mode can be selected:



a. There are four modes available:

- i. Automatic mode (green LED) - the door will open when a sensor is triggered and close after the preset dwell time has elapsed.
- ii. Hold open mode (Blue LED) – the door will open and remain open until another mode is selected.
- iii. Standby mode (Red LED) – the door can be manually operated, the AutoSlide will not drive the door.
- iv. Pet mode (Yellow LED) For use with AutoSlide pet sensors and when a pet opening width has been set (see below). Will open the door to the pet opening width when any AutoSlide pet sensor is triggered and close after the preset dwell time has elapsed.

b. The desired mode is selected by successive presses of the Mode button, to the right of the LED display. The modes will cycle in the order shown above (although the pet mode will be omitted if no pet opening width has been set). The selected mode will engage after a short delay.

INSTALLATION SET UP OPTIONS

These options require some thought ahead of the installation so the installing Engineer can leave the system configured to suit the requirement of the user and the site specific circumstances.

Wireless Push Switches (if fitted)

To be located somewhere within 20 metres of the door. Usually on the frame.

Push to open and close after a preset time period OR, push to open and stay upon until pushed again.

Movement Sensors (if fitted)

To be located somewhere within 1 metre of the door. Usually on the frame.

When activated; open and close after a preset time period OR, activated to open and stay open until activated again.

Pet Movement Sensors (if fitted)

To be located at low level somewhere within 1 metre of the door. Usually on the frame.

Activated to open to a preset width and close after a preset time period.

Pet Collar Tags (if supplied)

Sensors located at low level on the door frame.

Activated to open to a preset width and close after a preset time period.

Sound Warning

All sensors and switches BEEP upon activation OR remain silent.

SERVICE & MAINTENANCE

There is a 12 month parts and labour warranty included with the sale of a new system.

To ensure continued safe operation of the system it is strongly recommended that it is checked annually by a trained Installer.

A further 12 months (2 years total) parts only warranty is applicable; subject to the provision of a Service Visit Agreement.

Contact your Dealer/Supplier for details.

TROUBLE SHOOTING

- SYMPTOM: Door does not fully close
- CAUSE 1: The door movement is restricted
- SOLUTION 1: Clear any obstructions to ensure free movement of the door.
- CAUSE 2: System may have lost its learnt parameters or learnt the wrong ones.
- SOLUTION 2: Switch the system off at the mains, wait for a minute, ensure the doorway is free of obstructions and switch on again. The system will go through a learning cycle and should fully close
- SOLUTION 3: Contact ARXCIS Ltd on 0330 900 1230 (local rates)
- SYMPTOM: Door reopens after closing, judders or sounds noisy
- CAUSE: Rack and Pinion are losing engagement
- SOLUTION: Contact ARXCIS Ltd on 0330 900 1230 (local rates)
- SYMPTOM: Door is struggling to close or open and may reopen before fully closing.
- CAUSE 1: Lock may be engaged or partially engaged
- SOLUTION 1: Ensure door lock is fully retracted. AUTOSLIDE™ will only operate when door is unlocked.
- CAUSE 2: Friction in door has increased.
- SOLUTION 2: Contact ARXCIS Ltd on 0330 900 1230 (local rates)
- SYMPTOM: Door stops and blue, red, yellow lights illuminate.
- CAUSE: Over current trip due to excessive load on the door.
- SOLUTION: Contact ARXCIS Ltd on 0330 900 1230 (local rates)
- SYMPTOM: Door opens at random
- CAUSE 1: Radio interference
- CAUSE 2: Sensors too sensitive
- SOLUTION: Contact ARXCIS Ltd on 0330 900 1230 (local rates)

TECHNICAL SPECIFICATIONS

- Door Size: 2100 – 2400mm high x 720 – 1200mm wide
- Cover Colour: White stock colour. Black or bespoke colours upon request.
- Power Supply: 100-240V~50/60Hz
- Power Supply Output: 15-19Vdc/2A
- Safety Cut Off: YES
- Trained Domestic Use: YES
- Commercial Use: NO
- Drive Unit: 490mm long x 70mm high x 65mm deep
- AUTO or MANUAL Operation: YES



ARXCIS Ltd., Hammerain House, Harrogate, North Yorkshire HG2 8ER
Tel: 0330 900 1230 (local rates) Email: info@arxcis.co.uk Web: www.arxcis.co.uk